

Gravity Box Auger

*For Corn, Beans, and
Fertilizer*

Features:

Complete Maneuverability – Auger swings a full 180 degrees parallel and 90 degrees perpendicular to side of the box. Brake Winch and wire rope provided for easy regulation of discharge height

Versatility – designed so that the auger can be installed or removed from the wagon easily by means of 2 spring pins. Allows the auger to be used on several wagons with additional mounting kits.

Performance and Convenience –Hopper is funnel shaped for better movement of material, and the hydraulic motor and control valve are mounted on the discharge end for ease of operation. The support bracket carries auger parallel to the side of the wagon box for maximum clearance during travel

Quality Construction – Both the hopper and the flighting are heavy 10 GA steel. The center tube is 1" diameter high strength steel for years of trouble free operation.



Gravity box shown with
optional Lift Gate Adaptor

**Universal Hopper fits
openings 26" through 67"**

Standard Auger Lengths of 12' or 15'

Hydraulic or Electric Motor Drives

Hydraulic Motor Drive

Standard Auger includes hydraulic motor and hand control valve mounted on discharge end. Optional 12 Volt hydraulic solenoid valve with 15' long pushbutton pendant control available.

*Hydraulic requirements – 7GPM & 1500 PSI

Electric Motor Drive

Standard Auger includes 12 Volt electric motor, solenoid and 15" long pushbutton pendant control.

*Electric requirements - 12 Volt – 100 Amp alternator to be running while auger is in use.

*Electric auger **not** to be used for fertilizer or with bristle



Electric Motor shown with
solenoid and 15' pushbutton
remote control

Bloom Manufacturing Inc.

Power-Flite Division

1443 220th Street, Independence, Iowa 50644

FAX 319-827-1140 PHONE 319-827-1139



"Quality Since 1910"

POWER-FLITE

Gravity Box Auger Available Options

Optional Lift Gate Adaptors



Double Liftgate Adaptor



Single Liftgate Adaptor

The small opening allows operator greater control of flow into the hopper. An adjustment screw holds the door in a fixed position. Adjusts to fit a wide variety of door openings and can be easily removed when not in use. Double Lift Gate Adaptor helps to split wagon into two compartments.

Flighting Options

Bristle




Steel Cupped



Standard Cupped Steel Flighting is economical and efficient for most crop and fertilizer applications.

Optional Plastic Cupped Flighting also reduces damage to fragile seeds, has good wear characteristics.

Plastic Cupped



Optional Steel Core Bristle Flighting is especially good for fragile seeds, can dramatically reduce material damage

Contact us for what is best for your applications

Optional Remote control



solenoid with 15' pushbutton pendant control shown

Spouting Options

Optional Spout and Flexible Tube



Optional 3" Canvas Spout



Optional 3 piece Telescoping Downspout

Extends From 6' to 15'

